

Platform

The ULTRA SLIM Curved lift can be supplied with platforms from 750 x 600mm up to 1250 x 800mm and is suitable for internal or external applications.



The slip resistant surface of the platform ensures safe entry & exit of the lift. This surface is easy to clean allowing any water to drain off the platform. The lift has the option of an automatic platform,

Side Access

A side access platform is recommended for a stair with less than 3m of access at the lower landing. This option ensures that the user has sufficient room to manoeuvre on and off the platform safely. This is an optional extra that can be added onto your quotation.

All platforms are fitted with a pressure sensitive under tray and access ramps to stop the lift should it meet any obstruction on the stairs. These operate to prevent any damage to an obstruction or injury to people.



Automatic Wall Mounted
Call Station



Wanderlead Hand
Control

Operating Controls

The lift can be folded (automatic option) from any call station and called to any level. Up and down push buttons are provided on the platform for ease of use together with an emergency stop. An optional wanderlead is available to allow an attendant/carer to operate the lift.

The standard call controls will be surface mounted or stanchion mounted with the cables run in either surface mounted PVC conduit or mini-trunking. The option of flush mounted call controls is available; however, if hidden conduit runs are required they should be provided and installed together with draw wires, by the customer prior to installation.



Handheld Remote Key Fob

As an option, wireless call stations, key fobs and remote hand controls are available

Battery Back-up

Full Battery back-up is available as an option. This will allow for a number of cycles depending on the rail length.

Fold Down Seat



A fold down seat can be provided as an optional extra for those who find climbing the stairs a problem but who are not necessarily wheelchair users. The seat is folded down manually into position and we would recommend the optional wanderlead control for use with this option.

Colour

The Standard colours of the Ultra Slim Curved lift is RAL7035 Light Grey or RAL9005 Jet Black.

SAMPLE
RAL7035
Light Grey

SAMPLE
RAL9005
Jet Black

A non standard colour can be ordered in any colour from the RAL range. A stainless steel option is also available.



Lift is ideally suited for external use.

The Ultra Slim range can accommodate up to 225kg (35 stone)

Mains supply 240 volts 1 phase 50 Hz

All multi-flight lifts are custom built to your requirements. They are designed to be installed on virtually any type of staircase. The drive system allows the platform to turn corners, traverse half landings and negotiate straight and even spiral staircases smoothly and safely.

Standard or bespoke platform sizes
Suitable for internal or external use
Single and multi-flight capability

Rails

The rail system should be mounted on to a wall that is capable of withstanding a pull-out load of 8kN. If there are concerns as to the strength of the wall, or there is no wall available, the rails can be mounted on to stanchion posts. In order to use stanchion posts the treads and landings must be capable of withstanding a pull-out load of 22kN.



External Radius Bend



Wall Mounted Rails

Optional Extras

- Battery Back-up
- Fold Down Seat
- Wanderlead Control
- Flush Fitting Call Stations
- Stainless Steel Rails
- Non-Standard colour from the RAL Range
- Radio Operated Call Stations
- Post Mounted Call Stations
- Manual Fold Platform
- Side Access Platform
- Key Fob Remote Control



National Sales Enquiries

0845 600 5215

www.ecalifts.co.uk